

Interior Ceilings: Recommended Materials

	Exposed Roof and Floor Decks	Exposed Cast-in-place	Grid and Acoustical Tile	Paint (over gypsum board)	Metal Panels	Wood	Rapidly-Renewable Products
Group 1 HQ, Command, ECFs, Chapels							
Group 2 Admin. Squad Ops, Community Support							
Group 3 Industrial and Flightline Operations							
Group 4 Family Housing							

← Most Appropriate Least Appropriate →

General Notes:

1. Conduct a Life Cycle Cost Analysis: consider the cost of long-term maintenance and eventual replacement
2. Exposed steel roof decks and floor decks are preferred in Groups 1, 2 and 3 including high-visibility areas when systems are ordered, uncluttered, easy to keep clean and fully coordinated with fire sprinkler and other ceiling-mounted infrastructure and components
3. Exposed concrete may be used in Groups 1, 2 and 3 including high-visibility areas when systems are ordered, uncluttered, easy to keep clean and fully coordinated with fire sprinkler and other ceiling-mounted infrastructure and components
4. Limit gypsum board ceilings in Groups 1 and 2 to accents and wet rooms
5. Consider Federal HPSB Guiding Principles green product procurement requirements

EPA Resources: <http://www.epa.gov/>
<https://www.epa.gov/greenerproducts>
<http://www.biopreferred.gov/>